


LENGTH CODE CHART		
CABLE# & LENGTH	LENGTH SYMBOL	EXAMPLES OF PART# USED
CA-NMNMA XXX	WHERE XXX = LENGTH IN FEET	CA-NMNMA010 (10 FEET)
CA-NMNMA NXX	WHERE NXX = LENGTH IN INCHES	CA-NMNMAN16 (16 INCHES)
CA-NMNMA MXX	WHERE MXX = LENGTH IN METERS	CA-NMNMA07 (7 METERS)
CA-NMNMA XXM	WHERE XXM = LENGTH IN DECIMEL METERS	CA-NMNMA3M5 (3.5 METERS)

NOTES:

1. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY
2. CABLE ASSEMBLY SHALL RECIEVE INSERTION LOSS TEST#TP-0027
3. CABLE ASSEMBLY SHALL WITHSTAND PULL TEST OF 40lbs WITHOUT ANY SEPERATION OR ELECTRICAL FAILURE
4. CABLE SHALL BE RoHS COMPLIANT
5. CABLE SHALL BE INDIVIDUALLY PACKAGED IN HEAT SEALED POLY BAG WITH APPROP. LABEL (REF. DRAWING #F950)
6. CENTER PIN OF N-MALE CONNECTOR TO BE CRIMPED ONTO CABLE INNER CONDUCTOR

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES <u>OVERALL CABLE LENGTH TOLERANCE</u> ≤ 12 [305] = +1 [25]/-0 >12 [305] ≤ 60 [1524] = +2 [51] /-0 >60 [1524] ≤ 120 [3048] = +4/-4 >120 [3048] U+2264300 [7620] = +6/-0 >300 [76290] = +5%/-0					SIZE	TITLE:			
					A	FABRICATION: CA-195R SERIES N-MALE TO N-MALE ASSEMBLY with HEATSHRINK			
	REV	ECN No.	DATE	DESCRIPTION	DRAWN BY	B. Puchaski	06/27/08	DRAWING No.	REV
					ORIGINATOR	B. Puchaski	06/27/08	F947	A
 Website: www.L-com.com Tel: 1-800-343-1455 Copyright © 2009 L-com, Inc. All rights reserved.				APPROVAL	M. Audus	06/27/08	PART No.	CA-NMNMA	VAR.
				SCALE 1:1	SHEET 1/1	MATERIAL Noted	FILE No.	F947-01	